




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: G09G 3/00, G09F 13/30, 19/12	A1	(11) International Publication Number: WO 99/35634 (43) International Publication Date: 15 July 1999 (15.07.99)
(21) International Application Number: PCT/KR99/00023 (22) International Filing Date: 6 January 1999 (06.01.99) (30) Priority Data: 1998/76 6 January 1998 (06.01.98) KR (71)(72) Applicant and Inventor: JANG, Ji, Ho [KR/KR]; 26/8, 124-36 Namgajwa 1-dong, Seodaemun-gu, Seoul 120-121 (KR).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: DEVICE AND METHOD OF DISPLAYING IMAGES**(57) Abstract**

A device and method of displaying images using an afterimage caused by an optical illusion is disclosed. In the device, a controller (200) processes image data output from an image processing unit (100), thus generating an image display control signal and a motor control signal. A drive motor unit (400) rotates a rotary display assembly (300) at a speed in response to the motor control signal. A plurality of display units (320, 340, 360), individually designated to emit light beams at multi-angles, are orderly mounted on the rotary display assembly (300). The display assembly (300) is rotated at a speed by the drive motor unit (400) in response to the motor control signal while displaying images on the display units (320, 340, 360) at multi-angles in response to the image display control signal, thus forming desired images due to the afterimage caused by an optical illusion.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

-1-

DEVICE AND METHOD OF DISPLAYING IMAGES

Technical Field

The present invention relates, in general, to a
5 device and method of displaying images and, more
particularly, to a device and method of displaying
images due to an afterimage caused by an optical
illusion formed by rotating a rotary display assembly,
comprising a plurality of display units capable of
10 individually emitting light beams at multi-angles, at a
high speed.

Background Art

Several techniques for displaying images on a screen
have been well known to those skilled in the art. For
15 example, in the case of television receivers, a
plurality of electron beams are scanned from an electron
gun onto a screen, thus activating pixels on the screen
so as to form a desired picture thereon. Second, it is
also possible to form a desired picture on a screen by
20 projecting a film, having a developed image, on the
screen. That is, a film, with a developed image, is
projected by a projector onto a screen, thus forming a
desired picture on said screen. Third, a plurality of
LEDs (light emit diodes), constituting an LED display
25 board, may be used for displaying images. That is, the
LEDs of a display board are selectively turned on or off
under the control of a controller, thus forming a
desired picture on the board.

However, the above-mentioned typical techniques for
30 displaying images using television receivers, projectors
or LED display boards are problematic in that the images
are merely visible by viewers positioned within a
fixedly directed and limited area. Therefore, a person,
placed on an area out of the fixedly directed and

-2-

limited area, has a difficulty while seeing the image. In addition, the above techniques fail to allow a person, placed in the back of the screen, to see the pictures on the screen. Particularly, the known LED display boards, individually comprising a plurality of LEDs, are so large in their sizes and volumes, so that use of the LED display boards is undesirably limited to outdoor sign boards.

10 Disclosure of the Invention

Accordingly, the present invention has been made keeping in mind the above problems occurring in the prior art, and an object of the present invention is to provide a device for displaying images due to an afterimage caused by an optical illusion formed by rotating a rotary display assembly, comprising a plurality of display units capable of individually emitting light beams at multi-angles, at a high speed.

15 In order to accomplish the above object, the present invention provides a device for displaying images, comprising: a controller selectively processing image data output from an image processing unit so as to generate an image display control signal, the controller also generating a motor control signal; a drive motor unit selectively rotated at a speed in response to the motor control signal output from the controller; and a rotary display assembly comprising a plurality of image display units capable of individually emitting light beams at multi-angles, the assembly being rotatable at a speed by the drive motor unit and selectively displaying images on the display units in response to the image display control signal output from the controller.

30 Another object of the present invention is to provide a method of displaying images due to an afterimage caused by an optical illusion formed by

-3-

rotating a rotary display assembly, comprising a plurality of display units capable of individually emitting light beams at multi-angles, at a high speed.

5 In order to accomplish the above object, the present invention provides a method of displaying images, comprising the steps of: rotating a rotary display assembly at a speed by a drive motor unit while emitting light beams from a plurality of display units of the display assembly at multi-angles, thus forming an image
10 due to an afterimage caused by an optical illusion.

Brief Description of the Drawings

The above and other objects, features and other advantages of the present invention will be more clearly understood from the following detailed description taken
15 in conjunction with the accompanying drawings, in which:

Fig. 1 is a block diagram, showing the construction of an image display device in accordance with the preferred embodiment of the present invention;

20 Figs. 2 to 4 are views, respectively showing the construction of rotary display assemblies in accordance with different embodiments of the present invention;

Fig. 5 is a perspective view, showing an arrangement of display elements on each display unit of a rotary display assembly in accordance with the primary
25 embodiment of this invention;

Fig. 6 is a cross-sectional view of the display unit of Fig. 5;

30 Figs. 7, 8a, 8b and 8c are cross-sectional views of display units in accordance with the second, third, fourth and fifth embodiments of the present invention, respectively;

Figs. 9a to 9d are views, illustrating a method of accomplishing a high horizontal resolution of the image display device of this invention;

35 Fig. 10 is a view, illustrating a method of

-4-

accomplishing a high vertical resolution of the image display device of this invention; and

Figs. 11a to 11e are views, illustrating the horizontal resolving power of the image display device of this invention.

Best Mode for Carrying Out the Invention

Fig. 1 is a block diagram, showing the construction of an image display device in accordance with the preferred embodiment of this invention. As shown in the drawing, the device of this invention comprises an image processing unit 100, a controller 200, a rotary display assembly 300, a drive motor unit 400, and a power supply 500.

In the above display device, the image processing unit 100 may reproduce image data from an image storage medium, such as a compact disk, a video cassette tape or a hard disk, prior to transmitting the image data to the controller 200. The above processing unit 100 also may receive public waves, output from a broadcasting station, prior to transmitting image data of the public waves to the controller 200.

Upon receiving image data from the image processing unit 100, the controller 200 selectively processes the image data prior to generating an image display control signal. The above control signal is applied to the rotary display assembly 300 so as to allow said assembly 300 to display desired images. The controller 200 also generates a motor control signal. The motor control signal is applied to the drive motor unit 400 so as to rotate the display assembly 300 at a speed, at which the assembly 300 is rotated with about thirty display units 320, 340 and 360 passing a position in front of a viewer.

The rotary display assembly 300, comprising a plurality of display units 320, 340 and 360, displays

-5-

desired images on the display units 320, 340 and 360 in response to the image display control signal output from the controller 200. The drive motor unit 400 rotates the display assembly 300 at a speed in response to the
5 motor control signal output from the controller 200. The power supply 500 is used for supplying an electric power to each of the display units 320, 340 and 360 of the assembly 300.

That is, the rotary display assembly 300 is rotated
10 at a speed by the drive motor unit 400 under the control of the controller 200 while displaying images in response to an image display control signal output from the controller 200. In the present invention, the above assembly 300 may have a circular cross-section as
15 shown in Fig. 2. Alternatively, the rotary display assembly 300 may have a longitudinal oval cross-section as shown in Fig. 3. As a further alternative, the display assembly 300 may have a polygonal cross-section as shown in Fig. 4.

In the primary embodiment of this invention, each of the display units 320, 340 and 360 of the assembly 300 comprises a plurality of display elements 326 which are regularly arranged along a plurality of parallel and vertical rows on a flat mount panel 322, thus forming a
25 display element matrix as shown in Figs. 5 and 6. The rows of display elements 326 are separated from each other by a plurality of partition walls 324. That is, the rows of display elements 326 and the partition walls 324 are alternately arranged on one surface of the flat
30 mount panel 322. The alternately arranged display elements 326 and partition walls 324 are regularly and symmetrically inclined relative to the mount panel 322 at multi-angles of inclination, thus being directed in diverged radial directions. The display elements 326 of
35 each display unit 320, 340, 360 thus emit light beams at multi-angles.

Fig. 7 shows an arrangement of display elements 326

-6-

on each display unit 320, 340, 360 in accordance with the second embodiment of this invention. In the second embodiment, a plurality of display elements 326 are regularly arranged on one surface of a flat mount panel 322, thus forming a display element matrix. In such a case, the display elements 326 emit light beams in normal directions. One polarizing plate 328 is placed on the display elements 326, thus covering the display elements 326 and polarizing the light beams output from the elements 326. A plurality of partition walls 324 are regularly and symmetrically arranged on the polarizing plate 328 while being inclined relative to the polarizing plate 328 at multi-angles of inclination, thus being directed in diverged radial directions. Therefore, each display unit 320, 340, 360 according to the second embodiment emits light beams at multi-angles.

Fig. 8a shows an arrangement of display elements 326 on each display unit 320, 340, 360 in accordance with the third embodiment of this invention. In the third embodiment, one surface of the mount panel 322 is concaved from the top to the bottom so as to form an arc-shaped surface. A plurality of display elements 326 are regularly arranged along a plurality of parallel and vertical rows on the arc-shaped surface of the panel 322, thus forming a display element matrix. The rows of display elements 326 are separated from each other by a plurality of partition walls 324. That is, the rows of display elements 326 and the partition walls 324 are alternately arranged on the arc-shaped surface of the panel 322. The alternately arranged display elements 326 and partition walls 324 are regularly and symmetrically directed in converged radial directions, so that each display unit 320, 340, 360 emits light beams at multi-angles. Such an arrangement of display elements 326 according to the third embodiment preferably reduces the width of each display unit 320, 340, 360, thus allowing the rotary display assembly 300 to be more

-7-

precisely manufactured. Another advantage of the above arrangement resides in that it preferably accomplishes an image displaying angle larger than 180° .

Fig. 8b shows an arrangement of display elements 326 on each display unit 320, 340, 360 in accordance with the fourth embodiment of this invention. In the fourth embodiment, one surface of the mount panel 322 is concaved so as to form an arc-shaped surface in the same manner as that described for the third embodiment. A plurality of display elements 326 are regularly and symmetrically arranged along a plurality of parallel and vertical rows on the arc-shaped surface of the panel 322, thus forming a display element matrix with the display elements 326 being directed in converged radial directions. Two partition walls 324 are mounted on the panel 322 along both side edges of the arc-shaped surface in a way such that a slot is formed between the two partition walls 324 and allows the light beams from the display elements 326 to be radiated at multi-angles.

Fig. 8c shows an arrangement of display elements 326 on each display unit 320, 340, 360 in accordance with the fifth embodiment of this invention. In the fifth embodiment, a plurality of display elements 326 are regularly arranged along a plurality of parallel and vertical rows on a flat mount panel 322, thus forming a display element matrix. The display elements 326 are also symmetrically inclined relative to the mount panel 322 at multi-angles of inclination, thus being directed in converged radial directions. Two partition walls 324 are mounted on the panel 322 at both side edges of the panel 322 in a way such the two walls 324 are inclined inwardly at an angle of inclination with a slot being formed between the two partition walls 324. The slot of the two partition walls 324 allows the light beams from the display elements 326 to be radiated at multi-angles.

Figs. 9a to 9d illustrate a method of accomplishing a high horizontal resolution of the image display device

-8-

of this invention. As shown in the drawings, a plurality of display units, of which the multi-angles of both the display elements 326 and the partition walls 324 are different from each other, are continuously arranged on a rotary display assembly 300. When the rotary display assembly 300, carrying such display units, is rotated at a high speed, it is possible to form images having a high horizontal resolution.

Fig. 10 illustrates a method of accomplishing a high vertical resolution of the image display device of this invention. As shown in the drawing, a plurality of display units, of which the vertical intervals of the display element matrixes are different from each other, are continuously arranged on a rotary display assembly 300. When the rotary display assembly 300, carrying such display units, is rotated at a high speed, it is possible to form images having a high vertical resolution.

The operational effect of the present invention will be described hereinbelow.

In the operation of the above image display device, the image processing unit 100 may selectively process image data output from compact disks, video cassettes or hard disks prior to transmitting the processed image data to the controller 200. Alternatively, the image processing unit 100 may receive public waves, output from a broadcasting station, prior to processing image data of the public waves and transmitting the processed image data to the controller 200.

The controller 200 processes the image data output from the image processing unit 100 prior to generating an image display control signal, which is applied to the rotary display assembly 300 so as to allow said assembly 300 to display desired images. The controller 200 also generates a motor control signal used for rotating the assembly 300 at a desired speed, at which the assembly 300 is rotated with about thirty display units 320, 340

-9-

and 360 passing a position in front of a viewer.

That is, the drive motor unit 400 rotates the rotary display assembly 300 at a speed of not lower than 30 revolutions per second in response to the motor control signal output from the controller 200. When the rotary display assembly 300 is rotated by the motor unit 400 as described above, the assembly 300 displays desired images on the display units 320, 340 and 360.

In such a case, the power supply 500 supplies an electric power to each of the display units 320, 340 and 360 of the assembly 300.

Therefore, a viewer around the rotary display assembly 300 can see a desired image from the assembly 300 due to an afterimage caused by an optical illusion of the images formed on the display units 320, 340 and 360.

Figs. 11a to 11e are views, illustrating the horizontal resolving power of the image display device of this invention. When the display units 320, 340 and 360, individually emitting light beams at multi-angles, are orderly rotated as shown in Figs. 11a to 11c, it is possible to accomplish a desired horizontal resolving power at any position of a viewer as shown in Fig. 11e. In such a case, the horizontal resolving power is determined by the number of light beams emitted from the display elements 326 of the display units 320, 340 and 360.

For example, when a rotary display assembly 300, comprising a plurality of display units 320, 340 and 360 with both a plurality of display elements 326, individually having a 5mm width, and a plurality of partition walls 324 being arranged on each display unit 320, 340, 360 to form thirty different light emitting angles, is rotated at a high speed of not lower than thirty revolutions per second while displaying images on the display units 320, 340 and 360, a viewer around the assembly 300 can see thirty images at the same time due

-10-

to an afterimage caused by an optical illusion. When a plurality of image data are orderly moved through the display units of the assembly 300, the viewer can see thirty images at a fixed position.

5 When each display unit 320, 340, 360 of the rotary display assembly 300 only carries monochrome display elements, the display assembly 300 shows a monochrome image. However, each display unit 320, 340, 360 of the rotary display assembly 300 carries color display
10 elements or R (red), G (green) or B (blue) display elements, the display assembly 300 shows a color image when the assembly 300 is rotated at a high speed. When each display element 326, carried on each display unit 320, 340, 360, is designed to selectively emit R, G or
15 B color light beam, it is possible to form an image having a variety of colors due to an additive color mixture effect.

In the preferred embodiments of this invention, the display elements 326 are arranged on each display unit
20 320, 340, 360 of the rotary display assembly 300 in a way such that the display elements 326 emit light beams to the outside of the assembly 300. However, it should be understood that the display elements 326 may be arranged on each display unit 320, 340, 360 of the
25 assembly 300 in a way such that the display elements 326 emit light beams to the inside of the assembly 300. In such a case, a viewer, positioned inside the assembly 300, can see an image having an angle of 360°.

30 Industrial Applicability

As described above, the present invention provides a device and method of displaying images. The device of this invention displays a plurality of images having a high resolution using a rotary display assembly having
35 a circular, longitudinal oval or polygonal cross-section. The device is thus preferably used as an interior

-11-

instrument or a sign board in a store or an exhibit room.

5 The device of this invention also displays a plurality of images at multi-angles, thus preferably displaying several images or different program images at the same time. In addition, the device allows a plurality of users to play a multi-user game using one display device.

10 Another advantage of the invention resides in that since a plurality of display elements emit light beams at multi-angles when a plurality of display units are orderly rotated, it is possible to accomplish a desired horizontal resolving power at a position of a viewer, with the horizontal resolving power being determined by
15 the number of light beams emitted from the display elements of the display units.

Although the preferred embodiments of the present invention have been disclosed for illustrative purposes, those skilled in the art will appreciate that various
20 modifications, additions and substitutions are possible, without departing from the scope and spirit of the invention as disclosed in the accompanying claims.

-12-

Claims:

1. A device for displaying images, comprising:
 - a controller selectively processing image data output from an image processing unit so as to generate an image display control signal, said controller also generating a motor control signal;
 - a drive motor unit selectively rotated at a speed in response to the motor control signal output from said controller; and
 - 10 a rotary display assembly comprising a plurality of image display units capable of individually emitting light beams at multi-angles, said assembly being rotatable at a speed by said drive motor unit and selectively displaying images on said display units in response to the image display control signal output from the controller.
- 15 2. The device according to claim 1, wherein said display units of the rotary display assembly are arranged on the assembly so as to display images inside the assembly.
- 20 3. The device according to claim 1 or 2, wherein each of said display units comprises:
 - a mount panel concaved on one surface thereof from the top to the bottom, thus having an arc-shaped surface;
 - 25 a plurality of display elements regularly arranged along a plurality of parallel and vertical rows on said arc-shaped surface of the mount panel, thus forming a display element matrix and emitting light beams at multi-angles; and
 - 30 a plurality of partition walls positioned between the rows of display elements, thus separating the rows of display elements from each other and allowing the light beams, emitted from the display elements, to be

-13-

radiated at multi-angles.

4. The device according to claim 1 or 2, wherein each of said display units comprises:

a flat mount panel; and

5 a plurality of display elements regularly arranged along a plurality of parallel and vertical rows on one surface of said flat mount panel, thus forming a display element matrix with a plurality of partition walls being positioned between the rows of display elements, said
10 rows of display elements along with the partition walls being symmetrically inclined so as to emit light beams at multi-angles.

5. The device according to claim 1 or 2, wherein each of said display units comprises:

15 a mount panel concaved on one surface thereof from the top to the bottom, thus having an arc-shaped surface;

a plurality of display elements regularly and symmetrically arranged along a plurality of parallel and
20 vertical rows on the arc-shaped surface of the mount panel, thus forming a display element matrix and emitting light beams at multi-angles; and

two partition walls mounted on said mount panel at both side edges of the arc-shaped surface so as to form
25 a slot between them, said slot having a predetermined width and allowing the light beams, emitted from the display elements, to be radiated at multi-angles.

6. The device according to claim 1 or 2, wherein each of said display units comprises:

30 a flat mount panel;

a plurality of display elements regularly arranged along a plurality of parallel and vertical rows on said flat mount panel, thus forming a display element matrix and emitting light beams at multi-angles; and

-14-

two partition walls mounted on said flat mount panel at both side edges of the panel while being inclined inwardly at an angle of inclination, thus forming a slot between them, said slot having a predetermined width and allowing the light beams, emitted from the display elements, to be radiated at multi-angles.

7. The device according to claim 1 or 2, wherein each of said display units comprises:

a flat mount panel;

a plurality of display elements regularly arranged along a plurality of parallel and vertical rows on one surface of said flat mount panel, thus forming a display element matrix and emitting light beams in normal directions;

a polarizing plate covering the display elements so as to polarize the light beams emitted from the display elements; and

a plurality of partition walls regularly and symmetrically arranged on said polarizing plate so as to radiate the polarized light beams at multi-angles.

8. The device according to claim 3, wherein the light beam emitting angles of the display units are different from each other in accordance with the order of said display units, thus allowing the rotary display assembly to display an image having a high horizontal resolution when the display assembly is rotated at a high speed.

9. The device according to claim 3, wherein vertical intervals of the display element matrixes carried on the display units are different from each other, thus allowing the rotary display assembly to display an image having a high vertical resolution when the display assembly is rotated at a high speed.

-15-

10. The device according to claim 3, wherein the display elements of the display units individually and selectively emit a red, green or blue light beam, thus allowing the rotary display assembly to display a color image.

11. The device according to claim 3, wherein the display elements, carried on each of said display units, emit red, green or blue light beams, thus allowing the rotary display assembly to display a color image.

12. The device according to claim 1 or 2, wherein said rotary display assembly has a polygonal cross-section.

13. The device according to claim 1 or 2, wherein said rotary display assembly has a circular cross-section.

14. A method of displaying images, comprising the steps of:

rotating a rotary display assembly at a speed by a drive motor unit while emitting light beams from a plurality of display units of said display assembly at multi-angles, thus forming an image due to an afterimage caused by an optical illusion.

1/7

FIG.1





FIG.2



2/7
FIG.3






FIG.4



3/7
FIG. 5



4/7

FIG. 6





FIG. 7



5/7

FIG.8a




FIG.8b





FIG.8c



6/7





FIG. 10



7/7

FIG.11a




FIG.11b




FIG.11c




FIG.11d





FIG.11e



INTERNATIONAL SEARCH REPORT

International application No.
PCT/KR 99/00023

A. CLASSIFICATION OF SUBJECT MATTER		
IPC ⁶ : G 09 G 3/00; G 09 F 13/30, 19/12		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
IPC ⁶ : G 09 F 9/00, 13/00, 19/00; G 03 G 3/00		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
WPIL, EPODOC, PAJ		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	WO 90/12 354 A1 (STELLAR COMMUNICATIONS LIMITED) 18 October 1990 (18.10.90), fig.1,5,6,8,9; page 2, line 11 - page 3, line 36; page 7, paragraph 2 - page 8, paragraph 4; page 10, line 5 - page 11, paragraph 3; page 21, lines 13-35; claims 1,4,6-11,13.	14 1,3-6,8-13
A	WO 97/44 773 A1 (AVIX INC.) 27 November 1997 (27.11.97) & EP 0 844 598 A1 (AVIX INC.) 27 May 1998 (27.05.98), fig.; column 15, line 12 - column 17, line 26; claims 1-3.	1,3-6,8-11,14
A	EP 0 709 818 A1 (AVIX INC.) 01 May 1996 (01.05.96), fig.1,2; column 6, line 47 - column 9, line 24; claim 8.	1,3-6,8,9,14
A	EP 0 386 269 A1 (TOKIMOTO) 12 September 1990 (12.09.90), fig.16-21; page 2, lines 22-28; page 20, line 12 - page 27, paragraph 1.	1,3-6,8,9,14
A	WO 87/01 493 A1 (RAN DATA PTY. LTD.) 12 March 1987 (12.03.87), fig.1-4; abstract; page 9, paragraph 4 - page 11, paragraph	1,14
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
* Special categories of cited documents: „A“ document defining the general state of the art which is not considered to be of particular relevance „E“ earlier application or patent but published on or after the international filing date „L“ document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) „O“ document referring to an oral disclosure, use, exhibition or other means „P“ document published prior to the international filing date but later than the priority date claimed „T“ later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention „X“ document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone „Y“ document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art „&“ document member of the same patent family		
Date of the actual completion of the international search		Date of mailing of the international search report
26 April 1999 (26.04.99)		31 May 1999 (31.05.99)
Name and mailing address of the ISA/AT Austrian Patent Office Kohlmarkt 8-10; A-1014 Vienna Facsimile No. 1/53424/200		Authorized officer Wenninger Telephone No. 1/53424/325

INTERNATIONAL SEARCH REPORT

International application No.

PCT/KR 99/00023

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
	3; page 15, paragraph 3 - page 16, paragraph 3; claim 1,11.	
A	US 4 162 493 A (ROSS et al.) 24 July 1979 (24.07.79), fig.; claims 1,13,20.	1,14
P,A	Patent Abstracts of Japan, Vol.98, No.14, 31 December 1998 & JP 10-240182 A (FUJITSU KIDEN LTD.) 11 September 1998 (11.09.98).	14
A	US 5 020 882 A (MAKOW) 04 June 1991 (04.06.91), fig.1-7; column 4, line 45 - column 5, line 24.	7

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/KR 99/00023

In Recherchenbericht angeführtes Patentdokument Patent document cited in search report Document de brevet cité dans le rapport de recherche	Datum der Veröffentlichung Publication date Date de publication	Mitglied(er) der Patentfamilie Patent family member(s) Membre(s) de la famille de brevets	Datum der Veröffentlichung Publication date Date de publication
WO A1 9012354		AT E 109288 AU A1 54473/90 AU B2 644070 CA AA 2050891 DE C0 69011104 DE T2 69011104 DK T3 466795 EP A1 466795 EP B1 466795 ES T3 2061029 GB A0 8908322 JP T2 4504624 US A 5302965 WO A2 9012354 WO A3 9012354	15-08-1994 05-11-1990 02-12-1993 14-10-1990 01-09-1994 17-11-1994 21-11-1994 22-01-1992 27-07-1994 01-12-1994 01-06-1989 13-08-1992 12-04-1994 18-10-1990 29-11-1990
WO A1 9744773	27-11-1997	CA AA 2226479 EP A1 844598 JP A2 9311659	27-11-1997 27-05-1998 02-12-1997
EP A1 709818	01-05-1996	CN A 1121618 JP A2 8179717 JP B2 2802049 US A 5767822	01-05-1996 12-07-1996 21-09-1998 16-06-1998
EP A1 386269	12-09-1990	DE C0 68927881 DE T2 68927881 EP A4 386269 HK A1 1002036 JP A2 3074716 US A 5202675 EP B1 386269 JP A2 2213892 KR B1 9612286 WO A1 9005022 JP A2 2089089 JP B2 2865205 JP A2 2067589 JP B2 2868154 JP A2 3073995 JP B2 2648629	24-04-1997 10-07-1997 21-08-1991 24-07-1998 29-03-1991 13-04-1993 19-03-1997 24-08-1990 18-09-1996 22-03-1990 29-03-1990 08-03-1999 07-03-1990 10-03-1999 28-03-1991 03-09-1997
WO A1 8701493	12-03-1987	EP A1 270524 JP T2 63500746 US A 5027112 AU A1 46526785 AU B2 573024	15-06-1988 17-03-1988 25-06-1991 13-02-1986 26-05-1988
US A 4162493	24-07-1979	AU A1 21004/76 BR A 7700206 CA A1 1082825 CH A 618283 DE A1 2701277 DE B2 2701277 DE C3 2701277 ES A5 454929 ES A1 454929 FR A1 2338541 GB A 1521871 GR A 62457 IN A 147870 IT A 1082959 JP A2 52113129 JP B4 57027479 NL A 7700321 SE A 7700204	15-06-1978 20-09-1977 29-07-1980 15-07-1980 21-07-1977 15-03-1979 31-10-1979 04-03-1978 16-03-1978 12-08-1977 16-08-1978 12-04-1979 25-07-1980 21-05-1985 22-09-1977 10-06-1982 15-07-1977 04-08-1977
US A 5020882	04-06-1991	CA A1 1268271 US A 5122890	24-04-1990 16-06-1992

